

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

1. IDENTIFICATION OF SUBSTANCE OR PREPARATION AND OF COMPANY :

Identification of the product : A120 OIL (pn : 010990, 010991, 068099, 068844)

Use of the product : vacuum pump lubricant

Identification of the supplier :

adixen VACUUM PRODUCTS

98 avenue de BROGNY

BP 2069

74009 ANNECY CEDEX

FRANCE

Phone: +(33) 4 50 65 77 77

Fax: +(33) 4 50 65 77 89

Emergency telephone number: Poison control center Paris : +33 (0)1 40 05 48 48

2. IDENTIFICATION OF HAZARDS:

2.1 Classification of the substance or mixture

Product definition UVCB

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified

Classification according to Directive 67/548/EEC [DSD] Not classified.

2.2 Label elements

Hazard pictograms

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

2.3 Other hazards

Substance meets the criteria for PTB according to Regulation EC n° 1907/2006, Annex XIII No.

Substance meets the criteria for vPvB according to Regulation EC n° 1907/2006, Annex XIII No.

3. INFORMATION ON INGREDIENTS:

Substance/mixture UVCB

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/CEE	Regulation CE n° 1272/2008 [CLP]	
Distillates (petroleum), hydrotraeted heavy paraffinic	RRN: 01-211948462725 CE: 265-157-1 CAS: 64742-54-7	100	Not classified	Not classified	-

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

Annex I Nota L applies to the base oil(s) in this product. Nota L -The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

- Type
- [*] Substance
- [A] Constituent
- [B] Impurity
- [C] Stabilizing additive

4. FIRST AID MEASURES:

4.1 Description of first aid measures

Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist.
Inhalation from	If casualty is unconscious and: If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. In case of symptoms arising inhalation of product fumes, mists or vapor : Remove casualty to a quiet and well ventilated place if safe to do so. Seek medical assistance if breathing remains difficult.
Skin contact	Wash with soap and water. Remove contaminated clothing and shoes. Handle with care and dispose of in a safe manner. Seek medical attention if skin irritation, swelling or redness develops and persists. Accidental high pressure injection through the skin requires immediate medical attention. Do not wait for symptoms to develop.
Ingestion	Never give anything by mouth to an unconscious person. Seek professional medical attention or send the casualty to a hospital. Do not wait for symptoms to develop.
Protection of first-aiders potential is	No action shall be taken involving any personal risk or without suitable raining. Before attempting to rescue casualties, isolate area from all sources of ignition including disconnecting electrical supply. Ensure adequate ventilation and check that a safe, breathable atmosphere present before entry into confined spaces.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Irritation of the respiratory tract due to excess fume, mists or vapor exposure.
Skin contact	No known significant effects or critical hazards.
Ingestion	Ingestion(swallowing)of this material may result in an altered state of consciousness and loss of coordination.

4.3 Indication of any immediate medical attention and special treatment needed

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

For emergency responders

Small spillages:
normal antistatic working clothes are usually adequate.

resistance,

Large spillages:
full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical specifically to aromatic hydrocarbons.

Note :

gloves made of PVA are not water-resistant, and are not suitable for emergency use.

Safety helmet, antistatic non-kid safety shoes or boots.

Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated.

Respiratory protection :

(SCBA)

A half or full-face respirator with filter(s) for organic vapors (and when applicable for H₂S) a Self Contained Breathing Apparatus can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an deficiency is possible, only SCBAs should be used.

oxygen

6.2 Environmental precautions

Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials.

In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents.

If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means.

The use of dispersants should be advised by an expert, and, if required, approved by local authorities.

6.3 Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.

Large spill limit

Large spillages may be cautiously covered with foam, if available, to vapor cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

7. HANDLING AND STORAGE :

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

General information Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Use and store only outdoors or in a well-ventilated area. Avoid release to the environment.

7.1 Precautions for safe handling

Protective measures

Do not ingest. Use personal protective equipment as required.
Take precautionary measures against static discharge.
Avoid splash filling of bulk volumes when handling hot liquid product.
Avoid contact with skin. Avoid breathing fume/mist.
Prevent the risk of slipping.

for

Note: see section 8 for personal protective equipment and section 13 waste disposal.

Advice on general occupational hygiene

Ensure that proper housekeeping measures are in place.
Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets.
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
Wash hands thoroughly after handling.
Change contaminated clothes at the end of working shift.

7.2 Conditions for safe storage, including any incompatibilities

case of

Store in accordance with local regulations.
Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation.
Storage installations should be designed with adequate bunds in leaks or spills.
Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
Store separately from oxidizing agents.

containers

Recommended materials for containers, or container linings use mild steel, stainless steel.

Not suitable : Some synthetic materials may be unsuitable for or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer.

Keep only in the original container or in a suitable container for this kind of product. Keep containers tightly closed and properly labeled.
Protect from sunlight. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors.
Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

7.3 Specific end use(s) Recommendations

Lubricant
the

For more information regarding protective equipment and operational conditions see Exposure scenarios.

See appendix:

EXPOSURE ESTIMATION AND IDENTIFIED USES FOR "Other Base Oils, IP346 < 3%"

Input to Exposure Scenarios-4.2 Guidance to check compliance with exposure scenarios (environmental)

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

8. EXPOSURE INSPECTION / PERSONAL PROTECTION:

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name

Exposure limit values

No exposure limits value known.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

by

Derived effect levels

Product/ingredient name	Type	Exposure	Value	Population	Effects
Distillates(petroleum), hydrotreated heavy paraffinic	DNEL	Long term Inhalation	5,4 mg/m	Workers	Local

Predicted effect concentrations

No PECs available.

PNEC Summary

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

8.2 Exposure controls

Appropriate engineering Controls exhaust No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Individual protection measures

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation

location.

Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

Hand protection Wear oil-resistant protective gloves (e.g. nitril rubber). PVC neoprene

Body protection Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection should be approved by a specialist before handling this product.

Respiratory protection Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure Controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to process equipment will be necessary to reduce emissions to acceptable the levels.

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

9. PHYSICAL AND CHEMICAL PROPERTIES:

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Color	Light yellow
Odor	Odorless/Light petroleum.
Odor threshold	Not available.
pH	Not applicable.
Melting point/freezing point	-13C
Initial boiling point and boiling range	>400C
Flash point Closed cup:	247C [Pensky-Martens.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Burning time	Not applicable.
Burning rate	Not applicable.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	40 Pa @ 100 C
Vapor density	Not available.
Density	0,875 g/cm3 [15C]
Solubility(ies)	Insoluble in water. Soluble in most organic solvents.
Partition coefficient: n-octanol/ water	Not available.
Auto-ignition temperature	>270C
Decomposition temperature	>280C
Viscosity Kinematic (40C):	1,1 cm2/s (110 cSt)
Explosive properties	Not available.
Oxidizing properties	Not available.
DMSO extractible compounds for base oil substance(s) according to IP346	< 3%

9.2 Other information

No additional information.

10. STABILITY AND REACTIVITY:

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	Oxidizing agent.
10.5 Incompatible materials	Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. A mixture with nitrates or other strong oxidizers (e.g. chlorates, perchlorates, liquid oxygen) may create an explosive mass. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.6 Hazardous decomposition products

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

This may result in the evolution of harmful and flammable gases or vapors.

11. TOXICOLOGICAL INFORMATION:

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy	LC50 Inhalation Dusts and mists	Rat	>5,53 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Irritation/Corrosion

Skin Non-irritating to the skin.
Eyes Mild irritant
Respiratory Not available

Sensitizer

Skin Non-sensitizer to skin.

Reproductive toxicity

Conclusion/Summary Not considered to be toxic to the reproductive system.

Aspiration hazard

Not available.

Potential acute health effects

Inhalation Irritation of the respiratory tract due to excess fume, mists or vapor exposure.
Ingestion Ingestion (swallowing) of this material may result in an altered state of consciousness and loss of coordination.

Skin contact

No known significant effects or critical hazards.

Eye contact

Eye contact may cause redness and transient pain.

Potential chronic health effects

Chronic effects No known significant effects or critical hazards.

Carcinogenicity No known significant effects or critical hazards.

Mutagenicity No known significant effects or critical hazards.

Teratogenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

Other information Not available.

Specific hazard

12. ECOLOGICAL INFORMATION:

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Fish	96 hours
	Acute IC50 >100 mg/l	Algae	48 hours

Conclusion/Summary Aquatic toxicity data on base oils indicate LC50 values of > 100mg/l, which is considered as low toxicity.

12.2 Persistence and degradability

Conclusion/Summary Not readily biodegradable. Inherently biodegradable.

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

12.3 Bioaccumulative potential

Conclusion/Summary The product has a potential bioaccumulation.

12.4 Mobility in soil

Mobility Insoluble in water.

12.5 Results of PBT and vPvB assessment

PBT No.

VPvB No.

12.6 Other adverse effects

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

13. DISPOSAL CONSIDERATIONS :

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Waste treatment methods

Product

Methods of disposal used Where possible (e.g. in the absence of relevant contamination), recycling of substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorizations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organization, and/or prescribe composition limits and methods for recovery or disposal.

Hazardous waste Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

Packaging

Methods of disposal The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions according Care should be taken when handling emptied containers that have not been cleaned or rinsed out. These codes can be given only as a suggestion, to the original composition of the product, and its intended (foreseeable) use(s). The final user has the responsibility for the attribution of the most suitable code, according to the actual use(s) of the material, contaminations or alterations.

14 TRANSPORT INFORMATION :

International transport regulations

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

Other : -

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

15 REGULATORY INFORMATION:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV -List of substances subject to authorization

Substances of very high concern

None of the components are listed.

Annex XVII -Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Other EU regulations

Europe inventory

This material is listed or exempted.

Hazard class for water

1 Appendix No. 3

Greece

15.2 Chemical Safety

Assessment

Complete.

16 OTHER INFORMATION:

Exposure Scenario information

For more information regarding protective equipment and operational conditions see Exposure scenarios.

See appendix:

EXPOSURE ESTIMATION AND IDENTIFIED USES FOR "Other Lubricant Base Oils, IP346 < 3%" Input to Exposure Scenarios-4.2 Guidance to check compliance with the exposure scenarios (environmental)

Revision comments

Not available.

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE =Acute Toxicity Estimate
CLP = Classification, Labeling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Germany

Full text of abbreviated H statements

Not applicable.

Full text of classifications [CLP /GHS]

Not applicable.

Full text of abbreviated R phrases

Not applicable.

Full text of classifications [DSD/DPD]

Not applicable.

Date of printing

2011-02-21.

Date of issue/ Date of revision

2011-02-21.

Date of previous issue

No previous validation.

Version

1

Notice to reader

SAFETY DATA SHEET

Reference : SDS A120

According to directives 1907/2006 EEC

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described here in, we cannot guarantee that these are the only hazards that exist.